




2XSLCY-J MOTOR | 4G

Marking: <meters> CE 0987 SPECIALCAVI BALDASSARI 2XSLCY-J <formation> <lot> <year> ECA



MANUFACTURING CHARACTERISTICS

Conductor:

Flexible bare copper, class 5

Insulation:

XLPE compound

Stranding:

Cores stranded in concentric layers

Wrapping and protection:

Overall polyester tape

Shield:

1st shield:

Overall aluminium/polyester tape

2nd shield:

Overall tinned copper braid

Outer sheath:

Flame retardant PVC compound

Colours:

Cores identification:

Brown + Black + Grey + Green/Yellow

Outer sheath colour:

Transparent

ELECTRICAL CHARACTERISTICS

Nominal operating voltage: 0.6/1kV

Maximum operating voltage: 1.8kV D.C and 1.2kV A.C

Testing voltage: 4000V

APPLICATIONS

Cable conforms to the requirements in the Construction Products Regulations (CPR EU 305/11), aimed at limiting the production and diffusion of fire and smoke.

Shielded cable used to power motors with frequency converters when full electromagnetic compatibility (EMC) is required. Suitable for both static and dynamic connections (occasional movement) in industrial plants, process lines and machines operating in dry environments.

The cable must be protected from water and humidity.

Underground outdoor laying is not permitted even if protected.



STANDARDS

IEC 60228

REACTION TO FIRE CLASS

EN 50575:2016 E_{ca}

TEMPERATURES

Minimum working temperature:

- Fixed laying -25°C
- Occasional mobile laying w/o stress -5°C

Maximum working temperature:

- Fixed laying +90°C
- Occasional mobile laying w/o stress +90°C

Maximum short circuit temperature: +250°C

LAYING CONDITIONS



Minimum installation temperature -5°C



Min. bending radius: d8 (fixed laying) d15 (occasional mobile laying)



Max tensile stress: 50N/mm² (during installation) 15N/mm² (static stress)



Fixed laying



Occasional mobile laying w/o stress



In open air



In duct or cable tray



The cable must be protected from water and humidity

ON REQUEST

- Customized cores identification

2XSLCY-J MOTOR | 4G

PART NUMBER	FORMATION	OUTER DIAMETER ¹	WEIGHT ¹	MAX PHASE CONDUCTOR RESISTANCE AT 20°C
[n°]	[n° x mm ²]	[mm]	[kg/km]	[Ohm/km]
*2CXY15004	4 X 1.50	10.8	170	13.30
*2CXY25004	4 X 2.50	11.8	223	7.98
*2CXY40004	4 X 4.00	13.8	330	4.95
*2CXY60004	4 X 6.00	15.0	426	3.30
*2CXY100004	4 X 10.00	17.6	633	1.91
*2CXY160004	4 X 16.00	20.3	920	1.21
*2CXY250004	4 X 25.00	24.7	1382	0.78
*2CXY350004	4 X 35.00	27.5	1838	0.554
*2CXY500004	4 X 50.00	32.2	2563	0.386
*2CXY700004	4 X 70.00	37.9	3554	0.272
*2CXY950004	4 X 95.00	42.2	46.80	0.206
*2CXY1200004	4 X 120.00	47.3	5859	0.161
*2CXY1500004	4 X 150.00	52.8	7294	0.129
*2CXY1850004	4 X 185.00	58.3	8954	0.106
*2CXY2400004	4 X 240.00	66.3	11554	0.0801

^{*} According to in-stock availability, cable which must be produced on request and minimum quantity

¹ Unless otherwise specified, the values for weight and diameter are indicative.

Note: other values, if available and released for publication, are available on request.