




# 2XSLCYK-J MOTOR | 4G

Marking: &lt;meters&gt; CE 0987 SPECIALCAVI BALDASSARI 2XSLCYK-J &lt;formation&gt; &lt;lot&gt; &lt;year&gt; DCA-S3,D2,A3



## MANUFACTURING CHARACTERISTICS

**Conductor:**

Flexible bare copper, class 5

**Insulation:**

XLPE compound

**Stranding:**

Cores stranded in concentric layers

**Wrapping and protection:**

Overall polyester tape

**Shield:***1st shield:*

Overall aluminium/polyester tape

*2nd shield:*

Overall tinned copper braid

**Outer sheath:**

Flame retardant PVC compound

**Colours:***Cores identification:*

Brown + Black + Grey + Green/Yellow

*Outer sheath colour:*

Black (based on RAL 9005)

## ELECTRICAL CHARACTERISTICS

**Nominal operating voltage:** 0.6/1kV**Maximum operating voltage:** 1.8kV D.C and 1.2kV A.C**Testing voltage:** 4000V

## APPLICATIONS

Cable conforms to the requirements in the Construction Products Regulations (CPR EU 305/11), aimed at limiting the production and diffusion of fire and smoke.

Shielded cable used to power motors with frequency converters when full electromagnetic compatibility (EMC) is required. Suitable for both static and dynamic connections (occasional movement) in industrial plants, process lines and machines operating in dry and humid environments.

Direct or indirect underground outdoors laying is permitted (presence of water conduction AD7).

## STANDARDS

IEC 60228

## REACTION TO FIRE CLASS

*EN 50575:2016 D<sub>ca</sub> - s3, d2, a3*

## TEMPERATURES

**Minimum working temperature:**

- Fixed laying -25°C
- Occasional mobile laying w/o stress -5°C

**Maximum working temperature:**

- Fixed laying +90°C
- Occasional mobile laying w/o stress +90°C

**Maximum short circuit temperature:** +250°C

## LAYING CONDITIONS



Minimum installation temperature -5°C

Min. bending radius:  
d8 (fixed laying)  
d15 (occasional mobile laying)Max tensile stress:  
50N/mm<sup>2</sup> (during installation)  
15N/mm<sup>2</sup> (static stress)

Fixed laying



Occasional mobile laying w/o stress



In open air



In duct or cable tray



In buried trough



Buried with protection



In buried duct



Directly buried

## ON REQUEST

- Customized cores identification/outer sheath colours

**2XSLCYK-J** MOTOR | 4G

PART NUMBER	FORMATION	OUTER DIAMETER <sup>1</sup>	WEIGHT <sup>1</sup>	MAX PHASE CONDUCTOR RESISTANCE AT 20°C
[n°]	[n° x mm <sup>2</sup> ]	[mm]	[kg/km]	[Ohm/km]
*2CXJB150004	4 X 1.50	10.8	170	13.30
*2CXJB250004	4 X 2.50	11.8	223	7.98
*2CXJB400004	4 X 4.00	13.8	330	4.95
*2CXJB600004	4 X 6.00	15.0	426	3.30
*2CXJB100004	4 X 10.00	17.6	633	1.91
*2CXJB160004	4 X 16.00	20.3	920	1.21
*2CXJB250004	4 X 25.00	24.7	1382	0.78
*2CXJB350004	4 X 35.00	27.5	1838	0.554
*2CXJB500004	4 X 50.00	32.2	2563	0.386
*2CXJB700004	4 X 70.00	37.9	3554	0.272
*2CXJB950004	4 X 95.00	42.2	46.80	0.206
*2CXJB1200004	4 X 120.00	47.3	5859	0.161
*2CXJB1500004	4 X 150.00	52.8	7294	0.129
*2CXJB1850004	4 X 185.00	58.3	8954	0.106
*2CXJB2400004	4 X 240.00	66.3	11554	0.0801

\* According to in-stock availability, cable which must be produced on request and minimum quantity

<sup>1</sup> Unless otherwise specified, the values for weight and diameter are indicative.

Note: other values, if available and released for publication, are available on request.